

DURIP COPY

2

REPORT DOCUMENTATION PAGE

Form Approved
GSA No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 13 Mar 1990	3. REPORT TYPE AND DATES COVERED Final Report/1 Dec 88-30 Nov 89
----------------------------------	-------------------------------	---

4. TITLE AND SUBTITLE Experimental Testing of Corpuscular Radiation Detectors	5. FUNDING NUMBERS 61104D/3842/A6
--	--------------------------------------

6. AUTHOR(S)
Klaus W. Zieher

AD-A219 904

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Texas Tech University Department of Electrical Engineering P.O. Box 4439 Lubbock, TX 79409-4439	PERFORMING ORGANIZATION REPORT NUMBER AFOSR-TR-90-0357
--	--

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NP, BDA 410 Boiling AFB DC 20332-6448	10. SPONSORING/MONITORING AGENCY REPORT NUMBER AFOSR-89-0136
---	---

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.	12b. DISTRIBUTION CODE
---	------------------------

13. ABSTRACT (Maximum 200 words)
The equipment purchased under this DURIP grant is used in the Investigation of the Plasma Edge Cathode Scheme in support of grant AFOSR-87-0154. *Keywords:*
Corpuscular radiation

DTIC ELECTE
S MAR 29 1990 D
SE

14. SUBJECT TERMS High Speed Framing Camera Assembly, Image Scanner, RF-Enclosure <i>(Skins)</i>	15. NUMBER OF PAGES 2
--	--------------------------

17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR
---	--	---	-----------------------------------

16. PRICE CODE UL

FINAL TECHNICAL REPORT

DURIP Grant No. AFOSR-89-0036

(DURIP) HIGH SPEED CAMERA AND RF ENCLOSURE FOR INVESTIGATION OF PLASMA
EDGE CATHODE

Klaus W. Zieher
Department of Electrical Engineering
Texas Tech University
P.O.Box 4439
Lubbock, TX 79409-4439

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

13 March 1990

Prepared for

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFOSR)
Bolling Air Force Base
Washington, D.C. 20332



Research Projects:

The equipment purchased under D. RIP Grant No. AFOSR-99-0136 is used in the Investigation of the Plasma Edge Cathode Scheme. This research is supported by AFOSR Grant No. AFOSR-87-0154.

The High Speed Framing Camera Assembly has been constructed and assembled. It is dedicated to the analysis of the extracted electron beam from the plasma edge cathode. It records two images of the same event at different times at two separate locations on the film. Each image has a diameter of 35 mm on the film. The minimum exposure time is close to 5 nsec. The time delay between the two images can be adjusted starting from 0 nsec. The Image Scanner allows the evaluation of the recorded beam images inferring the shape of the effective plasma edge and the beam brightness of the electron beam.

The RF-Enclosure contains the recording oscilloscopes for two experiments investigating the electron extraction from the plasma edge and the investigation of the plasma jet itself (time-of-flight spectrometer). It also houses the data acquisition system for these two experiments. Electromagnetic signals generated by the plasma edge cathode experiment itself and by neighboring experiments are successfully shielded.